Appl. No. 09/525,615

Doc. Ref.: AR55

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

63-065587

(43) Date of publication of application: 24.03.1988

(51)Int.CI.

G06K 7/10

G06K 7/00

(21) Application number: 61-209879

(71)Applicant: MATSUSHITA ELECTRIC IND CO

LTD

(22) Date of filing:

05.09.1986


(72)Inventor: NAGASE HIROYUKI

(54) WIRELESS LIGHT PEN DEVICE

(57) Abstract:

PURPOSE: To connect the titled device to a data processor through radio by providing a circuit for binarizing the signal of a read barcode, an oscillating circuit and the modulating circuit of a carrier wave, and a chargeable battery, on a light pen device. CONSTITUTION: When a light beam emitted from a light emission

diode 1 is reflected by the white line part of a bar-code 3, the output of a phototransistor 2 becomes a 'white level'. This signal is amplified by an amplifier 5, also passes through a binarization circuit 6, becomes a binary data for signifying white, and a signal is supplied to a control circuit 4 and a modulating circuit 7. The output signal of the binarization circuit 6 is supplied to the modulating circuit 7, and a carrier wave signal oscillated by a carrier wave oscillating circuit 8 is modulated by the modulating circuit 7 and becomes a high frequency signal, and supplied to an antenna 9. In such a manner, by a signal obtained when the bar-code 3 is scanned, a carrier wave is modulated, and the read data of the bar-code 3 can be sent out by radio through an antenna.



LEGAL STATUS

[Date of request for examination]

Date of sending the examiner's decision of rejection

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

Date of requesting appeal against examiner's decision

of rejection]
[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office